blueriiot



Technical Sheet

Name	Blue Connect Go
Brand	Blueriiot
Manufacturer	Riiot Labs
Reference	73014
Dimensions	253 mm x 96 mm
Weight	714 g
Colors	Light grey (plastic) Blue (rubber)
Box content (see below)	1 x Blue Connect1 x Rubber cap1 x Fixing rope1 x Quick start guide
Protection Standard	IPx8 standard
Sensors	3-in-1 sensor
	pH: Measuring range: 0 to 14 Accuracy: ± 0.1 Resolution: 0.1
	Temperature: Measuring range: 5 to 50° C Accuracy: ± 0.2°C Resolution: 0.1° C
	Redox/ORP (platinum): Measuring range: 0 to 999 mV Accuracy: ± 20mV Resolution: 1 mV
Power supply	Replaceable Lithium Thionyl Chloride battery Lifetime: 24 months
Connectivity	Bluetooth Low Energy® (BLE), Sigfox® (available with subscription fee)
Sigfox radio configuration	RC1 868 MHZ Check the countries compatibility: https://build.sigfox.com/sigfox-radio-configurations-rc
Nominal voltage	3,6 V
Warranties	Blue Connect: 2 years Sensor: 2 years Battery: 1 year
Certifications	CE (blueriiot.com/legal)
Operating system (application)	iOS, Android (minimum required iOS 9.0 and Android 4.3) Bluetooth (minimum required 4.0 Bluetooth)
Application Languages	English, French, Spanish, Dutch, German, Italian, Portuguese, Czech, Swedish, Catalan, Polish.

